

unbalanced

Patch / Studio / Outdoor

AC104


Pro Audio Cable

- conductive plastic layer
- bare copper spiral shield




This robust, well shielded audio cable offers especially good handling due to its low external diameter. It is suited for high-impedance instruments as well as for wiring of Pedal boards and Line level devices.


Dieses robuste, gut geschirmte Audiokabel bietet durch seinen geringen Außendurchmesser ein besonders gutes Handling. Es eignet sich für hochohmige Instrumente ebenso wie für die Verkabelung von Pedalboards und Line-Level Geräten.

 Conductor	stranded bare copper, 7 x 0.20 mm
Cross Section	0.22 mm ²
Insulation	PE
1. Shield	conductive plastic layer
2. Shield	bare copper spiral shield
Outer Jacket	PVC, matt
Overall Diameter	6.1 mm

Leiteraufbau	blanke Cu-Litze, 7 x 0,20 mm
Leiterquerschnitt	0,22 mm ²
Isolation	PE
1. Schirm	leitende Kunststoffschicht
2. Schirm	blanker Cu-Wendelschirm
Außenmantel	PVC, matt
Außendurchmesser	6,1 mm

 Min. Bending Radius	30 mm
Working Temperature	-20 °C / +70 °C

Min. Biegeradius	30 mm
Betriebstemperatur	-20 °C / +70 °C

 Conductor Resistance	< 85 Ω/km
Capacitance	130 pF/m
Insulation Resistance	> 1 GΩ x km

Leiterwiderstand	< 85 Ω/km
Kapazität	130 pF/m
Isolationswiderstand	> 1 GΩ x km

■ SW [black] ■ BL [blue] ■ RT [red]

Order Code Bestell-Nr.	Colour Farbe	Weight Gewicht	Standard Length [m] Standard Längen [m]	Max. Length / Reel Max. Länge / Spule
AC104SW	black	45 g/m	100 / 500	3000 m
AC104BL	blue	45 g/m	100 / 500	3000 m
AC104RT	red	45 g/m	100 / 500	3000 m