

Accessories

Quick link Type A



No. 50301642 type A-50
 No. 50301643 type A-50 black
 No. 50301644 type A-90
 No. 50301646 type A-140
 No. 50301648 type A-200
 No. 5030164B type A-350

- Complies with DIN 56927:2009-03 • Form A (short)
- Galvanized • Test report according to DIN EN 10204 as download

Quick link Type B



No. 50301655 type B-90
 No. 50301659 type B-90 black
 No. 50301657 type B-140
 No. 5030165A type B-140 black
 No. 50301640 type B-200
 No. 5030165B type B-200 black

- Complies with DIN 56927:2009-03 • Form B (long)
- Galvanized • Test report according to DIN EN 10204 as download

Shackle 10mm



No. 58011058

Technical specifications:

Max. load WLL (5-fold):	1 t
Max. load BGV C1 (10-fold):	0.5 t
Identification:	3/8 WLL 1 t
Temperature range:	-20° C to +200° C
Standard:	DIN EN 13889:2009-02
Dimensions:	60 x 25 x 60 mm
Weight:	150 g

Shackle 16mm



No. 58011060

Technical specifications:

Max. load WLL (5-fold):	3.25 t
Max. load BGV C1 (10-fold):	1.6 t
Identification:	5/8 WLL 3 1/4 t
Temperature range:	-20° C to +200° C
Standard:	DIN EN 13889:2009-02
Dimensions:	107 x 95 x 38 mm
Weight:	680 g

Shackle 25mm



No. 58011065

Technical specifications:

Max. load WLL (5-fold):	8.5 t
Max. load BGV C1 (10-fold):	4.25 t
Identification:	SWL 8 1/2 t
Temperature range:	-20° C to +200° C
Standard:	DIN EN 13889:2009-02
Dimensions:	170 x 140 x 60 mm
Weight:	2250 g

Safety bond AG



No. 58010360 AG-5 3x600mm
up to 5kg

No. 58010364 AG-10 4x1000mm
up to 15kg

No. 58010368 AG-35FA 6x1000mm
up to 35kg

No. 58010369 AG-35FB 6x1000mm
up to 35kg

Saveking Safety bond 3x



No. 58010250 3x600, silver
 No. 58010252 3x600, black
 No. 58010254 3x1000, silver
 No. 58010256 3x1000, black

- Safety bond with integrated drop damping • BG certified
- Suitable for securing loads above persons • With two thimbles • 5 mm quick link (form B 140) included

Saveking Safety bond 4x



No. 58010258 4x600, silver
 No. 58010260 4x600, black
 No. 58010262 4x1000, silver
 No. 58010264 4x1000, black

- Safety bond with integrated drop damping • BG certified
- Suitable for securing loads above persons • With two thimbles • 6 mm quick link (form B 200) included

Saveking Safety bond 5x



No. 58010266 5x600, silver
 No. 58010268 5x600, black
 No. 58010270 5x1000, silver
 No. 58010272 5x1000, black

- Safety bond with integrated drop damping • BG certified
- Suitable for securing loads above persons • With two thimbles • Kettbinder (90 x 8, 200 kg) included

Safety bond A 3x600mm up to 5kg



No. 58010310 silver
 No. 58010342 black

- Suitable for securing loads above persons • Round strand rope 6x19M with fibre core • With two thimbles • 3.5 mm quick link (form A) included • Test report according to DIN EN 10204 as download

Safety bond A 4x1000mm up to 15kg



No. 58010320 silver
 No. 58010344 black

- Suitable for securing loads above persons • Round strand rope 6x19M with fibre core • With two thimbles • 4 mm quick link (form A) included • Test report according to DIN EN 10204 as download

Safety bond A 6x1000mm up to 35kg



No. 58010330 silver
 No. 58010346 black

- Suitable for securing loads above persons • Round strand rope 6x19M with fibre core • With two thimbles • 6 mm quick link (form A) included • Test report according to DIN EN 10204 as download

Safety bond B, black



No. 58010345 4x1000mm up to 15kg
 No. 58010347 6x1000mm up to 35kg

- Suitable for securing loads above persons • Round strand rope 6x19M with fibre core • With two thimbles • 4 mm quick link (form B) included • Test report according to DIN EN 10204 as download

Steel rope 400x3mm without quick link



No. 58010380 silver
 No. 58010382 black

- Suitable for installing light loads • With two loops

Technical specifications:

Max. load WLL (5-fold):	90 kg
Temperature range:	-40° C to +100° C
Rope length:	0.4 m
Rope diameter:	3 mm