

G308

G308

Compact 2-way full range system



- Extreme compact multidesign enclosure
 - Wide coverage angles
 - 1" patented compression driver
 - Multiple fly-points for easy hanging
 - Extended accessories range for both touring and installation
- System components: DNC260, C-Series Amplifiers, G15-SUB, G18-SUB

TECHNICAL SPECIFICATIONS G308

| | |
|---------------------|----------------------------------------------------|
| Type: | 2-way full range system, multidesign enclosure |
| Application: | High quality short throw |
| Frequency response: | 70 Hz - 30 kHz (-3 dB) |
| Power handling AES: | 220 W |
| Program power: | 440 W |
| Peak power: | 880 W |
| Sensitivity: | 94.5 dB |
| Max. SPL peak: | 124 dB |
| Dispersion: | 90° conical |
| Components: | |
| Low frequency: | 8" ultra low distortion cone driver, 2" voice coil |
| High frequency: | 1" compression driver, 1.5" voice coil |
| Crossover point: | 1900 Hz |
| Nominal impedance: | 8 Ohm |
| Input connectors: | 2x Neutrik™ NL4MP |
| Enclosure material: | Birch plywood |
| Suspension: | 2x M6 threaded points |
| Dimensions (WxDxH): | 230 x 471 x 260 mm |
| Net weight: | 9.5 kg |
| | Human EQ-switch |

The Coda Audio G308 is a compact versatile full range 2-way loudspeaker system that features an 8" ultra low distortion low frequency driver and a 1" compression driver coupled to a 90° conical wood waveguide.

The G308 incorporates a multidesign enclosure fitted with M6 flying points enabling it to be used horizontal, vertical or as a floor monitor.

ACCESSORIES

| | |
|---------|-------------------------------|
| FC308 | Flight case for 2 x G308 |
| A8VG | Vertical U-bracket for G308 |
| A8HG | Horizontal U-bracket for G308 |
| GFA | Flying Adapter for G308 |
| GSF | Stand fitting for G308 |
| M6 Ring | for rigging G308 |
| A68620 | Truss Clamp for G308 |