

G515-96**G515-96**

2-way high power full range multidesign



- 2-way compact versatile full range system
 - High power handling of 600 W
 - Neodymium drivers for light weight
 - 90° x 60° rotatable elliptical waveguide
 - Designed for both PA and stage monitoring
- System components: DNC260, C-Series Amplifiers, G15-SUB, G18-SUB

TECHNICAL SPECIFICATIONS G515-96

Type:	2-way full range system, multidesign enclosure
Application:	High quality short throw or stage monitor
Frequency response:	50 Hz - 21 kHz (-3dB)
Power handling AES:	600 W
Peak power:	2400 W
Sensitivity:	98 dB
Max. SPL peak:	132 dB
Dispersion:	90°x 60°
Components:	
Low frequency:	15" neodymium woofer, 3" (77 mm) voice coil, 600W (AES)
High frequency:	1" neodymium compression driver, 1.75" (44.4 mm) voice coil, 80W (AES)
Crossover point:	1200 Hz passive
Nominal impedance:	8 Ω
Input connectors:	2 x Neutrik™ NL4MP
Suspension:	M6 threaded points for use of optional U-bracket
Enclosure material:	15 mm birch plywood
Finish:	Textured black paint
Dimensions (WxHxD):	420 x 700 x 370 mm
Net weight:	17.5 kg
Weatherproof version:	Optional

The G515-96 is a versatile full range two-way loudspeaker system that features ultra low distortion 15" neodymium woofer and a 1" neodymium compression driver coupled to a 90° x 60° rotatable elliptical waveguide. The G515 incorporates a multidesign enclosure fitted with M6 threaded points for use with an optional U-bracket and includes an integral top hat. Applications include clubs, corporate events, FOH, stage monitor and band PA.

ACCESSORIES

A15VG	Vertical U-bracket for G515-96
A15HG	Horizontal U-bracket for G515-96
24481	Wall Mount for G515-96
GFA	Flying Adapter for G515-96
M6 Ring	for rigging G515-96
AK2G	Array kit for 2 x G515-96