

G715-96**G715-96**

3-way compact full range multidesign



- 3-way high output versatile full range system
- Unique 1,4" coaxial neodymium driver
- 90° x 60° rotatable elliptical waveguide
- 15" neodymium ultra low distortion woofer
- Passive or bi-amplified operation
- Designed for fixed installation, touring and stage monitoring

- System components: RC20 Rack, DNC260, C10, G18-SUB, SCP, SC4

TECHNICAL SPECIFICATIONS G715-96

Type:	3-way high power full range system, multi design enclosure
Application:	High output short/medium throw or stage monitor
Frequency response:	50 Hz - 21 kHz (-3 dB)
Power handling AES:	1000 W
Peak power:	4000 W
Sensitivity:	98 dB
Max. SPL peak:	134 dB
Dispersion:	90°x60°
Components:	
Low frequency:	15" neodymium woofer, 4" (101.6 mm) voice coil, 1000 W (AES)
High frequency:	1.4" neodymium coaxial driver, 3.5" (90 mm) + 1.75" (44.4 mm) voice coil, 150 W + 80 W (AES)
Crossover point:	750 Hz, 6.3 kHz passive
Nominal impedance:	8 Ω
Input connectors:	2 x Neutrik™ NL4MP
Suspension:	6 x M6 threaded points
Enclosure material:	15 / 18 mm Baltic birch plywood
Finish:	Textured black paint (all RAL-colours optional)
Dimensions (WxHxD):	420 x 700 x 370 mm
Net weight:	24.5 kg
Weatherproof version:	Optional

The Coda Audio G715-96 is a versatile full range 3-way loudspeaker system that features a high power 15" neodymium woofer and a 1.4" coaxial neodymium driver coupled to a rotatable 90° x 60° elliptical waveguide. As a 3-way system the G715-96 may be driven passively or with bi-amplification to provide extremely high acoustic output. The Audio G715-96 is a powerful solution for front of house touring, installed PA for theatres, clubs and corporate events or as a stage monitor.

ACCESSORIES

A15VG	Vertical U-bracket for G715-96
A15HG	Horizontal U-bracket for G715-96
24481	Wall Mount for G715-96
GFA	Flying Adapter for G715-96
M6 Ring	for rigging G715-96
AK2G	Array kit for 2 x G715-96