

## D5-Tube / D5-Ceiling



D5-Tube

D5-Ceiling



- Ultra compact 2-way coaxial system
- Coda Audio 5"/1" coaxial loudspeaker
- Attractive solid aluminum design

- Single point source system providing coherent wave front
- Superb quality sound
- Impedance 16 Ohm for easy daisy chaining

- System components: DNC260, C-Series Amplifiers, PW112, PW12A

## TECHNICAL SPECIFICATIONS D5-Tube

Type:	2-way coaxial ultra compact
Application:	Superior quality short throw
Frequency response:	90 Hz - 30 kHz (-3dB)
Power handling AES:	125 W
Program power:	250 W
Peak power:	500 W
Sensitivity:	91 dB
Max. SPL peak:	117 dB
Dispersion:	90° conical
Components:	
Low frequency:	5" woofer, 1.5" (38 mm) voice coil, 120 W (AES)
High frequency:	1" coaxially mounted driver, 1.75" (44.4 mm) voice coil, 80 W (AES)
Crossover point:	1600 Hz passive
Nominal impedance:	16 Ω
100V version (optional):	100 VA
Input connectors:	2x Neutrik™ NL4MP
Enclosure material:	Solid aluminum
Finish:	Metal (all RAL-colours optional available)
Weatherproof version:	Optional
Flying hardware:	M8 Thread
Dimensions (Ø x D) D5-Tube:	170 x 193 mm
Dimensions (Ø x D) D5-Ceiling :	170 x 193 mm, ceiling cut out Ø160 mm
Net weight:	4 kg

The Coda D5-Tube is a passive 2-way 5" / 1" coaxial loudspeaker system designed without compromise to provide a true one point source in an ultra compact package.

The D5-Tube incorporates an attractive cylindrical solid aluminum enclosure supplied with a U-bracket. The cabinet contains a high power 5" woofer and a coaxially mounted driver with 44.4 mm voice coil. The advanced design aligns the acoustical centers of the transducers to produce a single point source. This unique loudspeaker technology provides a coherent wave front without hot spots. Precise directivity of 90° conical ensures uniform coverage with perfect time alignment between the components.

Supported with a full range of mounting and flying accessories the D5-Tube sets a state of the art solution for almost any high quality, near field installed sound reinforcement applications, such as conference, restaurants, pubs, shopping centres, clubs, convention centres, houses of worship, airports and 5.1 surround.

Also available D5-Tube 100 V including 100 V trafo, 100 VA and D5-Ceiling for ceiling suspended installation.

## ACCESSORIES

CUV200	Vertical U-bracket for D5-Tube (included in delivery)
A68620	Truss Clamp for D5-Tube