**D8** 



## D8

2-way passive installation system

- Ultra compact 2-way coaxial system
- Coda Audio 8"/1" coaxial loudspeaker
- Single point source system providing coherent wave front
- Superb quality sound
- M6 flying points
- Improved transient response
- System components: DNC260, C-Series Amplifiers, PW115, PW118

The Coda D8 is a 2-way coaxial loudspeaker system designed without compromise to provide a true one point source in an ultra compact package. The cabinet contains

| TECHNICAL SPECIFICATIONS D8 |              |  |
|-----------------------------|--------------|--|
|                             |              | 2-way coaxial ultra compact                      |
|                             |              | Superior quality short throw                     |
|                             |              | 70 Hz - 20 kHz (-3 dB)                           |
|                             |              | 250 W  |
|                             | ogram power: | 500 W  |
|                             |              | 1000 W   |
|                             |              | 95 dB  |
|                             |              | 124 dB   |
|                             |              | 90° conical                                      |
|                             |              |  |
|                             |              | 8" neodymium woofer, 2" (52 mm) voice coil,      |
|                             |              | 250 W (AES)                                      |
|                             |              | 1" neodymium driver, 1.75" (44.4 mm) voice coil, |
|                             |              | 80 W (AES)                                       |
|                             |              | 1500 Hz passive                                  |
|                             |              | 16 Ω   |
|                             |              | 100 VA   |
|                             |              | 2x Neutrik™ NL4MP                                |
|                             |              | 12/15mm birch multiplex                          |
|                             |              | Textured black paint (all RAL-colors optional)   |
|                             |              |  |
|                             |              |  |
|                             |              |  |
|                             |              |  |
|                             |              |  |

a high power 8" woofer and a coaxially mounted driver with 44.4 mm voice coil. The advanced design aligns the acoustical centres of the transducers to produce a single point source. This unique loudspeaker technology provides a coherent wave front without hot spots. Precise directivity of 90° conical ensures uniform coverage with perfect time alignment between the components.

Also available D8 100 V including 100 V trafo, 100 VA.

Supported with a full range of mounting and flying accessories the D8 delivers a state-of-the-art solution for almost any high quality, near field installed sound reinforcement applications such as conference, theatres, clubs, convention centers, airports and 5.1 surround.

## ACCESSORIES

CU8DV CU8DH 24185 24171 195/8 M6 Ring Vertical U-bracket for D8 Horizontal U-bracket D8 Wall Mount for D8 Wall Mount for D8 Stand fitting for D8 for rigging D8