

PRO AUDIO IN MOTION HIGHLIGHTS CATALOG 2015



Within just a decade LD Systems® has become a major pro audio brand with an extensive range of product lines. The expert LD engineering team and highly motivated personnel are continuously engaged in creating advanced, state-of-the-art audio equipment that provides superior sonic performance and exceptional value. Designed in Germany, LD Systems® professional audio products deliver world-class sound around the globe.

LD Systems[®] is a brand of the Adam Hall[®] Group with headquarters near Frankfurt am Main, Germany. Established more than 35 years ago, the company has built a solid reputation for quality products, outstanding customer service and being a dependable partner in the pro audio, events and MI industries. The Adam Hall[®] Group's rigorous standards and dedication to innovation are reflected in each and every LD Systems[®] pro audio product.


Sound


smart, slim & **sophisticated**! THE **MAULSERIES** ACTIVE COMPACT COLUMN **PA SYSTEMS**



The active MAUI column systems by LD Systems offer an especially compact complete PA solution: they are very easy to transport, can be set up in seconds, and blend into any setting thanks to their unobtrusive appearance. The vertical array configuration, digital signal processing, and individualized amplification of the frequency bands by separate power amplifiers ensure an especially large dispersion angle and extremely homogeneous sound distribution in the audience area. With their impressive audio performance and simple handling, the LD MAUI PA systems are suitable for a surprisingly wide range of applications.

- ✓ Design PA for Musicians, DJs, Conferences
- Extended sound projection with reduced level drop off
- ✓ Wide and even sound dispersion (120° horizontal)
- ✓ Monitoring and PA in one / Feedback resistant
- ✓ Easy and quick setup, no cables required
- ✓ MAUI 44 : 3200 W (peak) / 1600 W (RMS) / Class D amplification incl. DSP
- ✓ MAUI 28 : 1600 W (peak) / Class A/B amplification
- ✓ MAUI 11 MIX : 1200 W (peak) / Class D amplification incl. DSP
- ✓ MAUI 28 & 11 MIX: Features an additional integrated 3-channel mixer
- ✓ V-construction subwoofers / Vertical array speaker column





(the second

LDMAUI11MIXW PA system active 121 dB 50 - 20000 Hz Class D 1200 W Peak 2 x 6.5" 8 x 3" / 1 x 1" Line input connectors: XLR, RCA, 1/4 inch Jack Mic: XLR, 1/4 inch Jack, MP3: 3.5 mm jack, Hi-Z: 1/4 inch Jack

MAUI **28** In White 1600 W Peak

Product number:

Product type: Max. SPL (peak): Frequency response: Amplifier: Power Output: Subwoofer: Mid/Hi System: Line input connectors: XLR, RCA, 1/4 inch Jack Line output connectors:: XLR

LDMAUI28W PA system active 123 dB 45 - 20000Hz 5-way Class A/B 1600 W Peak 2 x 8" 8 x 3" / 1 x 1"






Goliath Sound! DAVEG3 SERIES PORTABLE ACTIVE PA SYSTEMS

With four formats, the DAVE G3 Series by LD Systems always offers a correct choice for a very wide range of requirements. impressive sound, dependable performance, and convenient transport make the active subwoofer/satellite systems an ideal compact PA for demanding sound reinforcement tasks. The practical features also include the intelligent digital signal processor, which ensures optimal and constant reproduction.

✓ Compact active PA systems ✓ Up to 4800 W peak power Active subwoofer + 2 passive satellites

✓ Integral LD Systems LECC DSP

- ✓ Class-D / 3-way power amp module
- LD Systems "Evolutive" handles
- ✓ XLR/jack combo and RCA connectors
- ✓ 4 versions available: 10, 12, 15 or 18 inch subwoofer



you make it rock – **We make it roll! DAVE8ROADIE** COMPACT 8" PORTABLE **PA SYSTEM** WITH 3-CHANNEL MIXER

LN

With the DAVE 8 Roadie, LD Systems once again delivers "pro audio in motion". This complete PA system boasts a generous 1400 Watts peak power amp module and delivers astounding performance for all mobile applications.

10

DAVE 8 Roadie features 3 different inputs which can be used simultaneously. One channel with an XLR/jack-combo connector for dynamic microphones. One with dual RCA connectors for computers or XLR/1⁄4 inch jack-combo connector for mixing desks or keyboards, and one with stereo 3.5mm and mono 1⁄4 inch jack inputs which can be used for either an MP3 player or a guitar – a switch allows you to toggle between the two modes of this channel.

The rugged front grilles and ergonomic handles on both the subwoofer and the satellites underline the roadworthiness of the DAVE 8 Roadie and make it an ideal companion for musicians.

- \checkmark 2.1 PA System with Integrated class A/B amplifier module
- ✓ 1400 Watts peak power
- \checkmark Input channel 1: MP3 player input <-switchable-> Guitar input (Hi-Z)
- ✓ Input channel 2: Microphone input
- ✓ Input channel 3: Line Input (Keyboard, Mixer, Computer)
- \checkmark Mobile: Metal front grilles, carrying handles
- ✓ 8" Bandpass subwoofer
- ✓ 2 x 4" + 1" satellites (d'Appolito)
 ✓ 45 Hz 19000 Hz frequency response
- Transport bags available optionally
- \checkmark Speaker stands with cables bundle available optionally



the power to **surprise**! DAVE**8**XS

PORTABLE ACTIVE **PA SYSTEM**

SYSTEMS

The DAVE 8 XS delivers a crystal clear sound and was designed for all kinds of multimedia applications such as home recording, AV applications, DJ & Keyboard monitoring, PA for small sized public facilities (such as bars/pubs) etc. The class A/B amplification module integrated in the subwoofer delivers a high output and powers both sub and satellites. The LD DAVE 8 XS features XLR and RCA Phono-Line inputs, as well as all common protective circuits.

- ✓ 2.1 PA System with Integrated class A/B amplifier module
- ✓ 1400 Watts peak power
- ✓ Line Inputs: XLR / ¼ inch jack combo and RCA connectors
- 🗸 8" Bandpass subwoofer
 - 2 x 4" + 1" satellites (d'Appolito)
 - ✓ 45 Hz 19000 Hz frequency response
 - ✓ Transport bags available optionally
 - ✓ Speaker stands with cables bundle available optionally



hit the road! ROAD JACK SERIES NEW! ACTIVE BATTERY BLUETOOTH LOUDSPEAKERS WITH MIXER

The Road Series 8" and 10" active 2-way systems take your sounds anywhere. With built-in wheels and extension handles for carting convenience the LDRJ feature a 90 Hz - 18000 Hz frequency range and 100 watts peak output. A rechargeable battery pack provides up to 20 hours of continuous operation. The integrated mixer sports 3 channels with individual volume controls, a 2-band EQ plus adjustable reverb and master volume. Combo, 1/4 inch TRS jack, RCA and 3.5 mm TRS mini-jack connectors allow for a wide variety of input sources.

The LDRJ's major feature is a built-in Bluetooth player which permits wireless streaming to the system. It also supports SD card and USB storage devices. The player menu includes multiple genre specific presets for instant EQ adjustment. The LDRJ8 comes with a handy IR remote control and convenient stand mount insert.

- ✓ Portable battery powered Bluetooth® loudspeake
- ✓ Up to 20 h of continuous operation
- ✓ Built-in 3-channel mixer and media player with
- IR remote ✓ 2 band EQ and Echo
- Combo XLR/1/4 inch jack, RCA and mini jack inputs ✓ Supports Bluetooth® wireless streaming, SD card
- and USB storage devices

- 100 watts of Class D peak power 90 Hz – 18000 Hz (LDRJ8) /

- handle for convenient carting

Sound

- 65 Hz 18000 Hz (LDRJ10) frequency response Integrated wheels and extension



INGER **15** G

100

Quality 1 millisecond ahead... THE DDQ SERIES TOURING CLASS ACTIVE LOUDSPEAKERS AND SUBWOOFERS

Comprising 10", 12" and 15" active full-range speakers as well as 18" and 2 x 12" active subwoofers the LD Systems DDQ Series PA loudspeakers have been designed for the most demanding touring applications. Their comprehensive features and precision engineering deliver superior sound and reliable first-class performance with massive output levels up to 136dB (DDQ15) and 134dB (DDQ SUB18).

Loaded with premium speakers by FaitalPRO and BMS compression drivers, the DDQ Series is powered by Hypex Class D amplifier modules with high-efficiency SMPS, high continuous power capacity and dynamic response. The digital signal processing includes a peak limiter with 1ms look-ahead time for distortion-free audio, even at maximum levels.

Providing powerful low-end extension, the DDQ Series Subwoofers perfectly complement the DDQ full-range systems. With unique presets the DDQ SUB 18 and DDQ SUB 212 can easily be configured for vertical, stacked and end-fire cardioid subwoofer setups to deliver maximum SPL levels while reducing the rear sound projection of up to 20dB.

DDQ 10

- ✓ 800 Watts RMS
- Max SPL (peak): 132 dB
- 10" low/mid woofer + 1" tweeter
- ✓ Frequency range: 59 Hz 20000 Hz

DDQ 12

- ✓ 800 Watts RMS
- ✓ Max SPL (peak): 134 dB
- 12" low/mid woofer + 1" tweeter ✓ Frequency range: 54 Hz – 20000 Hz

DDQ 15

- 1400 Watts RMS
- ✓ Max SPL (peak): 136 dB
- ✓ Frequency range: 38 Hz 20000 Hz

DDO SUB 212

- 1400 Watts RMS
- Max SPL (peak): 132 dB
- ✓ 2 x 12" neodymium woofer
- ✓ Frequency range: 38 120 Hz
- ✓ 4 cardioid setups possible

DDQ SUB 18

- ✓ 1400 Watts RMS ✓ Max SPL (peak): 134 dB
- 18" neodymium woofer
- ✓ Frequency range: 30 120 Hz ✓ 4 cardioid setups possible

✓ Touring class powered PA speakers & subwoofers with Sharc DSP (24bit/48kHz) ✓ 1ms look-ahead time peak limiter

- ✓ State of the art analog/digital converters (127dB dynamic range)
- ✓ State-of-the-art Hypex Class D power stage modules
- ✓ 4 cardioid setups possible
- ✓ FaitalPRO neodymium woofers
- ✓ BMS compression drivers
- ✓ Rotatable asymmetrical HF horn flare
- ✓ Lightweight
- Made in Germany



nectar for your ears! **STINGERG2** SERIES PASSIVE / ACTIVE MULTIFUNCTIONAL SPEAKERS

LD Systems is unveiling the second generation of the successful STINGER family of speakers with a new design. In addition to outstanding value-for-money, the professional STINGER G² full-range PA systems with active and passive full-range speakers, subwoofers, and active monitors offers an appealing solution for all applications without compromises in terms of sound and reliability. The compact design is ideally suited for mobile use and elegant mounting in permanent installations.

Outstanding value for money

TINGER 8 G

- High-fidelity sound control
- BMS compression drivers
- Road-ready design with metal grille
- LD Systems "Evolutive" handles for a secure grip
- Dependable Class D power amp modules with limiter
- / Practical XLR/jack combo connectors
- Built-in M8 flyware mounting holes for increased flexibility
- / Transport covers, dollies, mounting brackets, and
- additional accessories available

get in the mix! STINGER MIX6(A)G2 NEW! 2-WAY LOUDSPEAKERS

The compact, lightweight Stinger MIX 6 A G2 active speaker features a 6.5" woofer and 1" HF transducer with a 80 Hz to 20000 Hz frequency response and 80° x 70° dispersion. It is perfectly suited for dedicated monitoring applications as well as small PA applications in combination with its dedicated slave speaker unit, the passive Stinger Mix 6 G2.


- ✓ tight and punchy bass reflex design
- y passive 2-way loudspeaker
- 280 watts peak power handling
- ✓ tight and punchy bass reflex design
- ✓ 6,5" woofer, 1" HF driver, 80 Hz 20000 Hz
- 2 pole mount inserts for vertical and horizontal orientation
- ✓ Stinger MIX 6 G2 ideal as a slave unit to LD Systems' Stinger MIX 6 A G2
- active 2-way loudspeaker ✓ integrated 4-channel mixer with EQ and 24-Bit DSP ✓ 560 watts peak power class D amplification with slave output
 - √ 6,5" woofer, 1" HF driver, 80 Hz 20000 Hz

 - 2 pole mount inserts for vertical and horizontal orientation











Installation



The slim compact installation speakers in the SAT G2 series by LD Systems blend discretely in practically any setting. This makes them suitable not only for commercial installation, e.g. in restaurants or retail shops, but also as a high-end home sound system. Suspension points, M6 inserts and variable mounting brackets offer many rigging options. The SAT G2 series subwoofers provide powerful and deep bass playback in passive and active versions.

An extremely versatile, Universal Mounting Bracket (SUWMB10), which is adjustable on all axes, is optionally available and allows secure installation of the SAT G2 speakers on walls and ceilings.

- Installation speakers & subwoofers Active & passive versions available White & black versions available
- ✓ XLR/ ¼ inch jack combo inputs (active versions)
- ✓ M6 fixing threads
 - Mounting brackets included
- Perfect for installations & home hi-fi application Discrete & reliable Spring terminal Input (passive versions)









2 x 1" Celestion HF drivers on waveguide 0° / 7° tilted

design meets **performance**

Die-cast aluminium body Convection cooling

16 x 3.5" neodymium fullrange speakers

Safe multi-pin connection

D amplifier modules (2 x sub, 4 x column)

6 x clas

Safe multi-pin connection

Ш

15 mm birch plywood

2 x 12" neodymium bandpass subwoofer PRO AUDIO IN MOTION

ACTIVE HIGH PERFORMANCE COLUMN **PA-SYSTEM**

- ✓ Design PA for musicians, DJs and business conferences
- ✓ 1,600 watts RMS / 129 dB peak SPL / 40 Hz 20000 Hz
- ✓ Extended sound projection with reduced level drop off
- Monitoring and PA in one / Feedback resistant
- Wide and even sound dispersion (120° horizontal)
- \checkmark Easy and quick setup, no speaker stands or cables required
- Powerful low resonance Bandpass subwoofer
- Crystal clear highs and detailed mids
- ✓ LECC DSP for distortion-free audio
- Protection circuits for secure, reliable operation
- ✓ Optional sub extension for enhanced bass experience (+6 dB)



FIND YOUR DEALER: WWW.**LD-SYSTEMS**.COM



The information contained in this publication, including numerical data, has been prepared as a general guide to the products, but intending buyers and users must satisfy themselves as to the suitability and the safety of the products for their particular purposes and duties. No responsibility is assumed for any errors herein. The company reserves the right to alter the designs and material specifications of products shown in this publication without notice.